

Electrically conductive castors














PE·VO·THAN® electrically conductive institutional castors












Series 68 XPU

Series 67 XPU/R

Series 67 XPU/P

										
Article code	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
67 XPU/075/24/1/P	75	24	100	60 x 60	48 x 48/38 x 38	6	–	30	60	
67 XPU/100/30/1/P	100	30	135	95 x 70	76 x 52/72 x 45	9	–	41	100	
67 XPU/125/30/1/P	125	30	160	95 x 70	76 x 52/72 x 45	9	–	39	125	
67 XPU/075/24/1/R	75	24	98	–	–	–	10	30	60	
67 XPU/100/30/1/R	100	30	132	–	–	–	12	41	100	
67 XPU/125/30/1/R	125	30	160	–	–	–	12	39	125	

Fixing devices for institutional swivel castors with bolt hole fitting, see page 133.

								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
68 XPU/075/24/1/P	75	24	100	67 x 60	48 x 48/38 x 38	6	60	
68 XPU/100/30/1/P	100	30	135	95 x 70	76 x 52/72 x 45	9	100	
68 XPU/125/30/1/P	125	30	160	95 x 70	76 x 52/72 x 45	9	125	

ALLSTOP total locking device
Code: 67 F XPU/.../P



single bolt hole/total lock
Code: 67 F XPU/...R




Institutional swivel castors with electrically conductive PEVOTHAN® wheels

Wheels series 85 XPU (80° Shore A) with plain bearing (/1), see page 80.

Institutional fixed castors

Matching the swivel castors with top plate (/P).












Institutional swivel castor brackets with a load capacity of up to 125 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearings and riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.










PE·VO·THAN® electrically conductive industrial castors




								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
31 XPU/080/35/3 L	80	35	108	105 x 85	80 x 60	9	38	100
31 XPU/100/34/3 L	100	34	128	105 x 85	80 x 60	9	38	140
31 XPU/125/37/3 L	125	37	155	105 x 85	80 x 60	9	45	180
31 XPU/150/45/3	150	45	194	135 x 110	105 x 80	11	55	225

Industrial swivel castors with electrically conductive PEVOTHAN® wheels

Wheels series 89 XPU (80° Shore A) with roller bearing (/3), see page 80.

								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
32 XPU/080/35/5 L	80	35	108	105 x 85	80 x 60	9	100	
32 XPU/100/34/5 L	100	34	128	105 x 85	80 x 60	9	140	
32 XPU/125/37/5 L	125	37	155	105 x 85	80 x 60	9	180	
32 XPU/150/45/5	150	45	194	135 x 110	105 x 80	11	225	

Industrial fixed castors












Industrial swivel castor brackets with a load capacity of up to 225 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearings, dust and splash proof, with riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

ALLSTOP total locking device Code: 31 F XPU/...	single bolt hole Code: 31 XPU/...R	single bolt hole/total lock Code: 31 F XPU/...R
		
foot protection Code: ...PRO	stem fitting Code: 31 Z XPU/...	stem fitting/total locking device Code: 31 FZ XPU/...
		










PE·VO·THAN® electrically conductive industrial castors



								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
51 XPU/080/35/5 L	80	35	108	105 x 85	80 x 60	9	38	120
51 XPU/100/40/5 GH	100	40	140	135 x 110	105 x 80	11	55	200
51 XPU/125/45/5	125	45	164	135 x 110	105 x 80	11	55	250
51 XPU/160/50/5	160	50	199	135 x 110	105 x 80	11	55	300
51 XPU/200/50/5	200	50	239	135 x 110	105 x 80	11	55	400


Industrial swivel castors with electrically conductive PEVOTHAN® wheels

Wheels series 87 XPU (96° Shore A) with ball bearings (/5), see page 81.

								
Article code	mm	mm	mm	mm	mm	mm	mm	kg
52 XPU/080/35/5 L	80	35	108	105 x 85	80 x 60	9	120	
52 XPU/100/40/5 GH	100	40	140	135 x 110	105 x 80	11	200	
52 XPU/125/45/5	125	45	164	135 x 110	105 x 80	11	250	
52 XPU/160/50/5	160	50	199	135 x 110	105 x 80	11	300	
52 XPU/200/50/5	200	50	239	135 x 110	105 x 80	11	400	

1-way directional lock not available for plate 105 x 85 mm.

Industrial fixed castors



Industrial swivel castor brackets with a load capacity of up to 400 kg

Housings made of pressed steel, zinc and chromated. Swivel head with double ball bearings, dust and splash proof, with riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

* with locking device code: 51 FZ XPU/...











ALLSTOP total locking device Code: 51 F XPU/...	single bolt hole Code: 51 XPU/...R	single bolt hole/total lock Code: 51 F XPU/...R
		
directional lock Code: 51 XPU/...1RIF	foot protection Code: ...PRO	stem fitting Code: 51 Z XPU/...*
		

PE·VO·LON® electrically
conductive industrial castors













Series WBX/5

Series WLX/5


									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
WLX 080/35/5 L	80	35	118	105 x 85	80 x 60	9	40	250	
WLX 100/40/5 L	100	40	140	105 x 85	80 x 60	9	45	350	
WLX 125/40/5	125	40	178	135 x 110	105 x 80	11	50	600	
WLX 150/50/5	150	50	205	135 x 110	105 x 80	11	50	600	
WLX 200/50/5	200	50	250	135 x 110	105 x 80	11	55	750	

Heavy-duty industrial
swivel castors with
electrically conductive
PEVOLON® wheels

Wheels series AX with ball
bearings (/5), see page 81.

									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
WBX 080/35/5 L	80	35	118	105 x 85	80 x 60	9	250		
WBX 100/40/5 L	100	40	140	105 x 85	80 x 60	9	350		
WBX 125/40/5	125	40	178	135 x 110	105 x 80	11	600		
WBX 150/50/5	150	50	205	135 x 110	105 x 80	11	600		
WBX 200/50/5	200	50	250	135 x 110	105 x 80	11	750		

Heavy-duty industrial
fixed castors




Industrial swivel castor
brackets with a load capacity
of up to 750 kg

Housings made of strong pressed
steel, zinc and chromated.
Swivel head with double ball
bearings, dust and splash proof.
Without kingpin. With grease
nipple. ALLSTOP total locking
device on the trailing side of the
housing, blocks rolling and swivel
motion simultaneously.

ALLSTOP total locking device
Code: WLFX...



foot protection
Code: ...PRO



4-way directional lock
Code: WLX...4RIF



wheel and directional lock
Code: WLFX...4RIF













PE·VO·THAN® electrically
conductive industrial castors



Series 68 XPU NI











Series 67 XPU NI/R

Series 67 XPU NI/P

									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
67 XPU NI/075/24/1/P	75	24	107	95 x 70	75 x 45/72 x 52	8	-	33	60
67 XPU NI/100/30/1/P	100	30	135	95 x 70	75 x 45/72 x 52	8	-	41	100
67 XPU NI/125/30/1/P	125	30	161	95 x 70	75 x 45/72 x 52	8	-	39	125

67 XPU NI/075/24/1/R	75	24	98	-	-	-	10	30	60
67 XPU NI/100/30/1/R	100	30	132	-	-	-	12	41	100
67 XPU NI/125/30/1/R	125	30	160	-	-	-	12	39	125

Fixing devices for institutional swivel castors with bolt hole fitting, see page 127.


									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
68 XPU NI/075/24/1/P	75	24	107	95 x 77	75 x 45/72 x 52	8	60		
68 XPU NI/100/30/1/P	100	30	135	95 x 77	75 x 45/72 x 52	8	100		
68 XPU NI/125/30/1/P	125	30	161	95 x 77	75 x 45/72 x 52	8	125		

Stainless steel institutional
swivel castors with
electrically conductive
PEVOTHAN® wheels

Wheels series 85 XPU
(80° Shore A) with plain
bearing (/1), see page 80.

Stainless steel institutional
fixed castors

Matching the swivel castors with
top plate (/P).



Institutional swivel castor
brackets with a load capacity
of up to 125 kg

Housings made of stainless
pressed steel. Swivel head with
double ball bearing and riveted
kingpin. ALLSTOP total locking
device on the trailing side of the
housing, blocks rolling and swivel
motion simultaneously.

ALLSTOP total locking device
Code: 67 F XPU NI/.../P



single bolt hole/total lock
Code: 67 F XPU NI/.../R













PE·VO·THAN® electrically conductive stainless steel industrial castors







Series 32 XPU NI/3R

Series 31 XPU NI/3R


									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
31 XPU NI/080/35/3R L	80	35	108	105 x 85	80 x 60	9	38	100	
31 XPU NI/100/34/3R L	100	34	128	105 x 85	80 x 60	9	38	140	
31 XPU NI/125/37/3R L	125	37	155	105 x 85	80 x 60	9	45	180	
31 XPU NI/150/45/3R	150	45	192	135 x 110	105 x 80	11	55	225	

Stainless steel industrial swivel castors with electrically conductive PEVOTHAN® wheels

Wheels series 89 XPU (80° Shore A) with stainless roller bearing (/3R), see page 80.

									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
32 XPU NI/080/35/3R L	80	35	108	105 x 85	80 x 60	9	100		
32 XPU NI/100/34/3R L	100	34	128	105 x 85	80 x 60	9	140		
32 XPU NI/125/37/3R L	125	37	155	105 x 85	80 x 60	9	180		
32 XPU NI/150/45/3R	150	45	192	135 x 110	105 x 80	11	225		

Stainless steel industrial fixed castors



Industrial swivel castor brackets with a load capacity of up to 225 kg

Housings made of stainless pressed steel. Swivel head with double ball bearings, dust and splash proof, with riveted kingpin. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.






ALLSTOP total locking device Code: 31 F XPU NI/...	single bolt hole Code: 31 XPU NI/...R	single bolt hole/total lock Code: 31 F XPU NI/...R
		
stem fitting Code: 31 Z XPU NI/...	stem fitting/total locking device Code: 31 FZ XPU NI/...	
		

PE·VO·LON® electrically conductive stainless steel industrial castors











Series WBX NI

Series WLX NI


									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
WLX NI/080/35/5R L	80	35	118	105 x 85	80 x 60	9	40	250	
WLX NI/100/40/5R L	100	40	140	105 x 85	80 x 60	9	45	350	
WLX NI/125/40/5R	125	40	178	135 x 110	105 x 80	11	50	600	
WLX NI/150/50/5R	150	50	205	135 x 110	105 x 80	11	50	600	
WLX NI/200/50/5R	200	50	250	135 x 110	105 x 80	11	55	750	

Heavy-duty stainless steel industrial swivel castors with electrically conductive PEVOLON® wheels

Wheels series AX with stainless ball bearings (/5R), see page 81.

									
Article code	mm	mm	mm	mm	mm	mm	mm	mm	kg
WBX NI/080/35/5R L	80	35	118	105 x 85	80 x 60	9	250		
WBX NI/100/40/5R L	100	40	140	105 x 85	80 x 60	9	350		
WBX NI/125/40/5R	125	40	178	135 x 110	105 x 80	11	600		
WBX NI/150/50/5R	150	50	205	135 x 110	105 x 80	11	600		
WBX NI/200/50/5R	200	50	250	135 x 110	105 x 80	11	750		

Heavy-duty industrial fixed castors



Industrial swivel castor brackets with a load capacity of up to 750 kg

Housings made of strong stainless pressed steel. Swivel head with double ball bearings, dust and splash proof. Without kingpin. With grease nipple. ALLSTOP total locking device on the trailing side of the housing, blocks rolling and swivel motion simultaneously.

ALLSTOP total locking device Code: WLFX NI/...
